

The company,

**The Size Surfaces, S.L.**

P.I. Camí Fondo, Supoi 8.  
C/dels Ibers, 31  
12550 Almazora (Castellón)  
Spain

Declares that:

The product **Neolith anti-slip** manufactured at its facilities, can be offered in the anti-slip varieties mentioned in table 1 and it comes with the following guarantees:

- The application of the anti-slip treatment does not change the tonality of the surface.
- Once installed, the product is guaranteed for 2 years provided that the installation of the Neolith anti-slip material meets a number of conditions:
  - ✓ Install the floor in a clean way.
  - ✓ Thoroughly clean the glue remnants without scratching the surface and without the use of abrasive products. A cleaner for antislip treated floorings is recommended.
  - ✓ Avoid impregnating the treated floor with cement or cementitious adhesives, etc.
  - ✓ Once the floor is installed, to maintain its characteristics, the "*Cleaning protocol for Neolith anti-slip pavement.*" should be followed (annex)

NORM	METHOD	FINISH				
		SATIN	SILK	RIVERWASHED	POLISHED*	NATURAL HONED
ENV 12633	Pendulum	3	2	3	1	1
DIN 51097	Critical angle barefoot	C	B	C	A	A
DIN 51130	Critical angle with footwear	R9	R9	R10	< R9	< R9

Table 1. Anti-slip properties after treatment.

Almazora, September 2016

  
**THE SIZE SURFACES, S.L.**  
 B-85171023  
 P.I. CAMÍ FONDO, SUPOI 8, C/ DELS IBERS Nº 31  
 C.P. 12550 ALMAZORA (CASTELLÓN)

\* Loss of glossiness

ANNEX I

## CLEANING PROTOCOL FOR NEOLITH ANTI-SLIP PAVEMENT

### DAILY CLEANING

- Cleaning products: pH neutral products in order to avoid degradation of the antislip treatment.
- Cleaning method: Mechanical cleaning with sweeping or scrubbing machines with absorption of liquids.

### WEEKLY CLEANING

- Cleaning products: Use of a non-aggressive disinfectant (we advise against the direct use lye), a product that eliminates lime scale and minerals or ammonia.
- Cleaning method: Mechanical brushing to remove the lime scale or minerals residue.

### MONTHLY CLEANING

- Cleaning products: Nonslip floor cleaners like the "*Special cleaner anti-slip treated floors*" from Johnson Spain S.L. Antideslizantes Division to assist in the removal of microbial or bacteriological residue and help to maintain the anti-slip areas.
- Cleaning method: Brush the area with the product, leaving the cleaning product to act, rinse and collect the liquid.